

# DuraTech®



## D2C Series Control Stations with Factory Sealed Contacts for Classified Locations

- Non-metallic controls for Class I, Division 2, Groups A, B, C, D locations and corrosive areas.
- Constructed of rugged polyester resin and gasketed for NEMA 4X hose down protection.
- Factory sealed contacts rated for heavy duty NEMA A600/Q300 explosion-protected operation.
- Comprehensive selection of operators:
  - Push buttons, standard or mushroom caps, momentary & maintained action for multiple function or emergency stop.
  - Rotary selector switches, maintained or momentary operation.
  - Pilot lights, multiple voltage & color (LED standard).
- Multiple options for various enclosure entry types and legend plates.

## Combat Excessive Moisture and Corrosion in Hazardous and Hostile Environments



Petro Chemical Plants



Coastal Areas



Waste water Treatment



Food Processing



**KILLARK®**  
A Division of Hubbell Incorporated (Delaware)

# DuraTech®

## D2C Series Control Stations



Factory Sealed  
Contact Block  
1 N.O./1 N.C.

Class I, Division 2, Groups A, B, C, D  
Class I, Zone 2, Groups IIC, IIB, IIA  
NEMA 3, 4, 4X, 7 (Div. 2)

UL US Certified

### Applications

This product is suitable for facilities where the presence of hazardous atmospheres and corrosive environments may exist.

### D2C Materials

- Enclosures & operators
  - PBT polyester resin
- Gaskets
  - Neoprene/EPDM blend
- Cover screws
  - 316 Stainless Steel (captivated)

ONE OPERATOR:					
SINGLE PUSH BUTTON (Momentary Contact)					
COMPLETE UNITS (Box & Cover) DEAD-END	NPT SIZE	DIAGRAM		COLOR	LEGEND
D2CG2B1	3/4"			GREEN	START
D2CG2B2				RED	STOP
D2CG2B3				BLACK	BLANK
PUSH-PULL MUSHROOM BUTTON (Maintained Contact)					
D2CG2MMR3	3/4"			RED	EMERGENCY STOP
PILOT LIGHT (120V AC Light Emitting Diode Type)					
D2CG2B24RL	3/4"			RED	BLANK
2 POSITION ROTARY SELECTOR SWITCH (Maintained Contact)					
COMPLETE UNITS (Box & Cover) DEAD-END	NPT SIZE	LEFT	DIAGRAM CENTER	RIGHT	LEGEND
D2CG2S2A3	3/4"		-		OFF - ON
3 POSITION ROTARY SELECTOR SWITCH (Maintained Contact)					
D2CG2S3C3	3/4"				HAND-OFF-AUTO
TWO OPERATORS:					
TWO PUSH BUTTONS (Both Momentary Contact)					
COMPLETE UNITS (Box & Cover) DEAD-END	NPT SIZE	DIAGRAM		COLOR	LEGEND
D2CG2B4	3/4"			GREEN - RED	START-STOP
D2CG2B7				BLACK - BLACK	BLANK
PILOT LIGHT (120V AC LED) AND PUSH BUTTON (Momentary Contact)					
D2CG2B13	3/4"			RED LENS, BLACK BUTTON	BLANK
THREE OPERATORS: ** Specify pilot light lens marking, if required					
PILOT LIGHT (120V AC LED) AND TWO PUSH BUTTONS (Both Momentary Contact)					
COMPLETE UNITS (Box & Cover) DEAD-END	NPT SIZE	DIAGRAM		COLOR	LEGEND
D2CG8B15	3/4"			RED LENS, GREEN & RED BUTTONS	START-STOP
THREE PUSH BUTTONS (Each Momentary Contact)					
D2CG8B9	3/4"			GREEN & RED & BLACK BUTTONS	START-STOP, BLANK

NOTE: Special markings (if required) on blank legend plates may require additional lead time.



**KILLARK®**  
A Division of Hubbell Incorporated (Delaware)